

## Blue Hammer Anchor Testing Data\*

Product Information				Tested in Concrete of 4,000 psi			
Diameter	Length	Part	Box	Weight	Embedment	Tension (lb)	Shear (lb)
1/4	1-3/4	52560	100	3.16	1-1/8	1050	1750
	2-3/8	52561	100	3.85	1-1/8	1050	1750
5/16	2-3/4	52562	50	3.64	1-1/2	1780	2190
3/8	2-3/8	52563	50	4.55	2-1/2	2390	2780
	3-1/2	52564	50	6.36	2-1/2	2390	2780
	4-3/4	52565	50	7.90	2-1/2	2390	2780
1/2	2-3/4	52566	25	5.23	3	3320	5400
	3-1/2	52567	25	5.80	3	3320	5400
	4-3/4	52568	25	7.37	3	3320	5400
	6	52569	25	9.00	3	3320	5400
5/8	4	52570	10	4.21	2-3/8	5200	6090
	4-3/4	52571	10	4.99	2-3/8	5200	6090
	6	52572	10	6.88	2-3/8	5200	6090
3/4	5	52573	10	7.68	3-1/2	8500	7000
	6	52574	10	8.78	3-1/2	8500	7000
	7-1/2	52575	10	10.56	3-1/2	8500	7000

**Midwest Fastener Corp.**  
**9031 Shaver Road**  
**Portage, MI 49024-6164**  
**Tel: 1-800-444-7313**  
**Fax: 1-800-388-9798**  
**Email: saleshelp@mwf.net**

*\*Anchors were tested by an independent, A2LA accredited laboratory. Midwest Fastener Corp. states the results of these tests without making any performance claims.*

**\*\*All necessary safety factors are not applied to this data. Please consult with your local building code office for safety factor requirements.**



Flyer #399072